

SUBMITTAL DATA SHEET

CH-18MSPHCT-230VI

Job Name:
 Location:
 Engineer:
 Submitted to:
 Submitted by:
 Reference:

Date:
 Approval:
 Construction:
 Unit #:
 Drawing #:



PERFORMANCE AND EFFICIENCY

Cooling		Heating	
18,000 Btu/h		18,000 Btu/h	
SEER	20	COP	3.2
EER	12.5	HSPF	10.5

OPERATION TEMPERATURE RANGE

cooling	heating
62~90°F	32~86°F

ELECTRICAL

Power supply	208-230V/ 60Hz, 1Ph
MCA	15 A
MFA	20 A
Fan motor	
Input	45 W
RLA	1.5 A

MCA: Minimum Circuit Ampacity **MFA:** Max. fuse A **RLA:** Rated load A

PIPING

Refrigerant piping Liquid/Gas side	1/4 - 1/2 in
------------------------------------	--------------

This warranty should be registered on our web-site www.cooperandhunter.us within 60 days of installation. The warranty is only valid when installed by a Licensed HVAC Technician. A warranty period of Seven (7) years on compressor to the original registered end-user. A warranty period of Five (5) years on all parts to the original registered end user. Warranty applies only to products remaining in their original installation location.



GENERAL FEATURES

- Activated Carbon Filter
- Mute Operation
- Sleep Mode
- 12 Grades Indoor Fan Speeds
- Self Diagnosis Function
- Two-way Draining Connection
- Golden fin for outdoor and indoor
- Two Direction Airflow
- Double Level Air Flaps
- High Density Filter
- Turbo Operation
- Refrigerant Leakage Detect
- Emergency Using Function

INDOOR SPECIFICATION

Air Flow (Hi/Mi/Lo)	562/485/439 CFM
Noise Level (Hi/Mi/Lo)	46/43/41 dB(A)
Unit Dimension(WxDxH)	22.44x22.44x10.24 in
Net/Gross Weight	39.68/46.3 lb

SUBMITTAL DATA SHEET

CH-18MSPHCT-230VI

