

18 GALLON
ELECTRIC POINT OF USE WATER HEATER

GE20P08BAR



FEATURES AND BENEFITS

Stainless Steel Heating Elements: Ultra-durable, low-watt-density heating elements resist rust and corrosion.

Anode Rod: A durable design offers long-lasting protection against corrosion to prolong the water heater's life.

Compact Design: Ideal in limited spaces like kitchens, bathrooms, laundry rooms, cabins, RVs, garages, sheds, and more.

Straightforward Connection: The heater connects right into a 120-Volt supply.

Leading Warranty: 8-year limited replacement or 8-year tank and parts/ 1-year labor warranty for peace of mind.



INSTALLATION INFORMATION

LOCAL INSTALLATION REGULATIONS:

This water heater must be installed in accordance with these instructions, local codes, utility codes, utility company requirements or, in the absence of local codes, the latest edition of the National Electrical Code. It is available from some local libraries or can be purchased from the National Fire Preventions Association, Batterymarch park, Quincy, MA 02169 as booklet ANSI/NFPA 70.

INSTALLATION INFORMATION:

For complete information, see installation instruction packed with your water heater.

POWER REQUIREMENTS:

Check the markings on the rating plate of the water heater to be certain the power supply corresponds to the water heater requirements.

LOCATION:

Locate the water heater in a clean dry area as near as practical to the area of the greatest heated water demand. Long uninsulated hot water lines can waste energy and water.

REQUIRED CLEARANCES:

There must be sufficient clearance between any object and the top, rear and sides of the water heater in the event service is needed. The controls and drain at front of unit must have clear access for operation and service. Installations that require minimal clearance on the sides or rear of the water heater for earthquake straps are also acceptable. In these cases, additional clearance should be provided on the opposite side of the unit to allow for service access

For answers to your GE Profile™ or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center® Service 800.626.2000.



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

DIMENSIONS AND SPECIFICATIONS

GE20P08BAR
RealMAX CHOICE



RATINGS/POWER	
Rated Capacity (Gallons)	18
Product Application	Residential
Wall Mount Or Freestanding	Freestanding
Fuel Type	Electric
Heating Element (Watts)	1,500
Voltage	120
Current (Amps)	12
Power Cord Included	Yes
Power Cord Length (Ft.)	6
Anode Rod	Aluminum
Mechanical Temperature Control	Yes
Temp Range	70-140° F
Temp Settings Default	120° F
Connection Sizes— Cold Water Inlet/Hot Water Outlet (Mnpt)	3/4"
Element Material	Stainless steel
INTEGRATED SAFETY DEVICES	
T&P Valve	Yes
T&P Valve Location	Top
Drain Valve	Yes
Drain Valve Location	Bottom-Side
Drain Valve Material	Glass-filled nylon
WEIGHTS & DIMENSIONS	
Product Height (In.)	25.75
Product Width (In.)	19.25
Product Depth (In.)	19.25
Product Weight (Lbs.)	54.25
Carton Height (In.)	28.75
Carton Width (In.)	23.50
Carton Depth (In.)	22.75
Shipping Weight (Lbs.)	62
WARRANTY	

8yr Tank and Parts/ 1yr Labor

POINT OF USE WATER HEATERS

Point of use setups are flexible, adaptable, and space-saving. Their compact design is ideal for limited spaces like kitchens, bathrooms, laundry rooms, cabins, RVs, garages, and sheds, and in some cases, can also provide hot water for a small house, condo, or apartment. Typically, these easy-to-install heaters fit right under the kitchen, bathroom, or pantry sinks and connect into a standard 120-Volt outlet (cord included).



Listed by
Underwriters
Laboratories



Certified to
NSF/ANSI 372
See http://info.nsf.org/Certified/Load_Content/
for specific model listing



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

©Copyright 2024 GE Appliances, a Haier Company. Our continued commitment to quality products may mean a change in specifications without notice.