

Pro-Flex™ Special Termination Plate



PFST-Series

ITEM # SUBMITTED: _____
JOB NAME: _____
LOCATION: _____
ENGINEER: _____
CONTRACTOR: _____
PO #: _____
TAG: _____

APPLICATION

The Pro-Flex™ Special Termination Plate is used to eliminate the need for concealed fittings by allowing CSST to be routed to the exterior of the wall or floor to provide a fixed connection point (stub-out). The fixed connection points allows for the attachment of flexible appliance connectors to moveable appliances such as dryers and ranges.

INSTALLATION

Product installation and system testing shall be completed by a qualified installer in accordance with NFPA 54/ANSI Z223.1 (National Fuel Gas Code), National Gas & Propane Installation Code B149.1 (Canada), state/local codes and the Pro-Flex Installation/ Training Guide.

MATERIALS

FITTING & NUT: 360 Brass

O-RING: Silicone Rubber

RETAINER & SLIDE RINGS: ASTM A240/A240M 304 Stainless Steel

HIGH TEMP GASKET: Non-asbestos proprietary material

PLATE: Galvanized Steel

SPECIFICATIONS

APPROVED GASES: **Natural Gas and LP [Propane] Gas**

TEMPERATURE RATING: -20° F/ -28.9° C—200° F/ 93.3° C

MAX WORKING PRESSURE: 25 PSIG

MAX TEST PRESSURES:

Nominal Diameter	Maximum Test Pressure
1/2"	150 PSI
3/4"	150 PSI
1"	125 PSI
1 1/4"	100 PSI



CODES, STANDARDS & LISTINGS:

Codes: NFPA 54, ICC Codes [IFGC, IRC, IPC, IMC], UPC, CAN/CSA B149.1

Standards: ANSI LC1• CSA 6.26

Listings: CSA Master Contract 1174673, IAPMO File # 3669

DIMENSIONAL DATA:

Item Number	Qty Per Box	Plate Dimension	Inlet	Outlet
PFST-12	6	4" x 2.50"	1/2" ProFlex	1/2" MIP - 3/8" FIP
PFST-34	6	4" x 2.50"	3/4" ProFlex	3/4" MIP - 1/2" FIP
PFST-01	6	4" x 2.50"	01" ProFlex	01" MIP - 3/4" FIP



Pro-Flex™
Traditional CSST

Pro-Flex LLC

FlakJacket™
Arc-Resistant CSST

www.proflexcsst.com

HearthMaster™
Gas Valves, Keys & Bars

1-877-798-6291

Pro-Poly™
Underground Gas Piping